



RS26L+

i-SYNERGY
Cleaning Management in Motion

Rider Auto Scrubber

The RS26L+ rider scrubber, designed for large floor surface areas, is fully automated with a one button programmable switch for training-free operation, and a three-setting pad pressure of up to 165 lbs. for maximum cleaning efficiency.

Our state-of-the-art fleet management software, i-Synergy, provides real-time access to valuable data including location, operating times, charging times, and confirmed clean—all through user-friendly reports that can be emailed directly to you.

The RS26L+ features a digitized (1% to 5%) solution mixing system making solution composition changes simple, and the compact design makes it easy to maneuver in a variety of spaces.


RS26L+

Benefits

- Reduce machine downtime with active maintenance from our dedicated team of technicians
- Monitor your machine locations and performance through i-Synergy Fleet Management
- Increase efficiency and performance through easy to read cleaning reports
- Confirm clean with interested stakeholders through downloadable cleaning reports
- Improve cleanliness with our oversized 26 gallon solutions tank
- Ensure staff and building occupant safety with our lithium-ion batteries
- Save time and money training staff with all-inclusive training and user friendly equipment



Touchscreen Interface



- | | |
|---------------------|-----------------------|
| Modes | Current Mode |
| 1.7 Hr Timer | Detergent |
| Fault Indicator | Pressure |
| F↑ Forward/Reverse | Lights On/Off |
| Setting | Solution Flow Control |
| Vacuum Motor Switch | |

Technical Specifications

Model Type	USA	RS26L+ I-SYNERGY
Voltage	VOLT	24
Cleaning Path	INCH	26
Traction Drive System	TRACTION	FORWARD/BACKWARD
Number of Brushes	PCS	2
Brush Rotation Speed	RPM	210
Brush Motor	V/WATT	24/2x450
Brush Pressure	LB	76-122-165
Squeegee	INCH	41.2
Solution Tank	GALLON	29
Recovery Tank	GALLON	29
Batteries	V/AH	24/225
Type Batteries	STANDARD	LI-ION
Sound Level	DBA	68
Weight without batteries	LB	703
Weight with batteries	LB	704
Run Time per charge	HOURL	3.5 - 4
Cleaning Productivity	FT ² /HR	50,697
Sizes	LXWXH INCH	62x34, 5x55.5
Gradeability	%	17