



# RS28-0B

## 28" Rider Scrubber Orbital

The RS28-0B rider auto scrubber is fully automated with a one-button programmable switch for training-free operation, and a three-setting pad pressure of up to 165lb allows for maximum cleaning efficiency. Its digitized (1% to 5%) solution mixing system makes solution composition change simple, and the compact design gives the RS28-0B maximum maneuverability.

# RS28-0B

## Benefits

- One button programmable switch for training-free operation
- On-board digital solution mixing system improves working efficiency
- Touch panel control system is state-of-the-art and user friendly
- Heavy-duty construction for maximum durability
- Lifetime parts warranty on orbital deck isolators
- No tools needed for changing parabolic squeegee blades
- Variable pad pressure up to 165 lbs
- Automatic braking and parking
- Emergency shutdown system and safety lighting
- Compact design enables cleaning of narrow aisles and tight areas with maximum maneuverability



## Technical Specifications

Model Type	USA	RS28-0B
Voltage	VOLT	24
Cleaning Path	INCH	28
Traction Drive System	TRACTION	FORWARD/BACKWARD
Number of Brushes	PCS	2
Vacuum Motor	HP	0.6
Brush Motor	V/WATT	559
Brush Pressure	LB	80/120/160
Squeegee	INCH	40
Solution Tank	GALLON	29
Recovery Tank	GALLON	29
Batteries	V/AH	4x6 V, 305 AH@20HR
Type Batteries	WET FLOODED	AGM
Sound Level	DBA	68
Weight without batteries	LB	640
Weight with batteries	LB	900
Run Time per charge	HOURL	4
Cleaning Productivity	FT <sup>2</sup> /HR	49,500
Travel Speed	MILE/HR	4
Sizes	LXWXH INCH	61.6x31.5x56.7
Grade Level, Max	%	7 - SCRUBBING 17.5% - TRANSPORTING (EMPTY)
Minimum Aisle Turn	INCH	75