



RS28-0B

Orbital Rider On Scrubber

The RS28-0B is 28" cylindrical rider scrubber designed for large floor surface areas, is fully automated with a one button programmable switch for training-free operation, and a three-setting pad pressure of up to 160 lbs. for maximum cleaning efficiency. It has orbital scrubbing technology that offers a deeper, more uniform clean as well as chemical free stripping.

Downtime is wasted time. Money spent on replacement parts takes away from your bottom line. At ICE USA, we understand that you use our machines as hard as possible to do your job, and we recognize that sometimes maintenance is a necessity. That's why our auto scrubbers come with a 5 year warranty. We have faith that we provide the best equipment possible, but if anything happens— we're here for you.

RS28-OB

Benefits


- One button programmable switch for training-free operation
- On-board digital solution mixing system improves working efficiency
- Touch panel control system is state-of-the-art and user friendly
- Heavy-duty construction for maximum durability
- Lifetime parts warranty on orbital deck isolators
- No tools needed for changing parabolic squeegee blades
- Variable pad pressure up to 160 lbs
- Automatic braking and parking
- Emergency shutdown system and safety lighting
- Compact design enables cleaning of narrow aisles and tight areas with maximum maneuverability

Touchscreen Interface



   Modes

 1.7 Hr Timer

 Fault Indicator

 Forward/Reverse

 Setting
 Vacuum Motor
 Switch

 1 Current Mode

 Detergent

 Pressure

 Lights On/Off

 Solution Flow Control

Technical Specifications

Model Type	USA	RS28-OB
Voltage	VOLT	24
Cleaning Path	INCH	28
Traction Drive System	TRACTION	FORWARD/BACKWARD
Number of Brushes	PCS	2
Vacuum Motor	HP	0.6
Brush Motor	V/WATT	559
Brush Pressure	LB	80/120/160
Squeegee	INCH	41
Solution Tank	GALLON	29
Recovery Tank	GALLON	29
Batteries	V/AH	4x6 V, 305 AH@20HR
Type Batteries	WET FLOODED	AGM
Sound Level	DBA	68
Weight without batteries	LB	640
Weight with batteries	LB	900
Run Time per charge	HOURL	4
Cleaning Productivity	FT ² /HR	49,500
Travel Speed	MILE/HR	4
Sizes	LXWXH INCH	61.6x32x56.7
Grade Level, Max	%	7 - SCRUBBING 17.5% - TRANSPORTING (EMPTY)
Minimum Aisle Turn	INCH	75

